

vaal Steam

FOR YOUR TOTAL INDUSTRIAL PACKAGE

VAAL STEAM SUPPLIES (PTY) LTD • Reg. No. 1980/004973/07

A BEE COMPANY

ISO9001:2008 Certified Company

Gasket Material

ACID - 200

Application

Premium quality acid jointing non asbestos material. A chemical grade material suitable for most acids, alkalies, oils, fuels and refrigerants for aggressive environments.

Dimensions of

standard sheets: 1500 mm X 1500 mm,
1500 mm X 2250 mm,
1500 mm X 4500 mm

Specification: ASTM F104 F 712000 A9 M5

Technical data: All data are typical values and refer to sheet thickness of 1.5 mm

OIL - 220

Application

Suitable for oils, fuels, lubricants, alcohols, gases, hydrocarbons, steam, water, cooling liquids, most diluted acids and alkalies for medium stress conditions - non asbestos material.

Dimensions of

standard sheets: 1500 mm X 1500 mm,
1500 mm X 2250 mm,
1500 mm X 4500 mm

Specification: ASTM F104 F 712122 E32 A9 B6 M5

Technical data: All data are typical values and refer to sheet thickness of 1.5 mm

STEEL - 350

Application

Excellent thermal, chemical & mechanical properties internal combustion engines and alkalies for high stress conditions - non asbestos material.

Dimensions of

standard sheets: 1500 mm X 1500 mm,
1500 mm X 2250 mm,
1500 mm X 4500 mm

Specification: ASTM F104 F 712111 E12 A9 B6 M6

Technical data: All data are typical values and refer to sheet thickness of 1.5 mm

350 - C

Application

Suitable for oils, fuels, lubricants, alcohols, gases, hydrocarbons, steam, water, cooling liquids, most diluted acids and alkalies for medium stress conditions - non asbestos material.

Dimensions of

standard sheets: 1500 mm X 2000 mm,
1500 mm X 4000 mm

Specification: ASTM F104 F 712111 E22 A9 B5 M5

Technical data: All data are typical values and refer to sheet thickness of 1.5 mm

Tel: +27 (0)16 421 1278/81
e-mail: info@vaalsteam.co.za



FOR YOUR TOTAL INDUSTRIAL PACKAGE